Managed Switch

SMC6708L2 INT

TigerSwitch™ 10/100 Standalone 8-port 10/100 Managed Switch

OVERVIEW

SMC6708L2 INT is an intelligent standalone Fast Ethernet Switch with 8 auto-MDIX 10BASE-T/100BASE-TX ports. With an aggregated bandwidth of up to 1.6Gbps, it has a non-blocking switching architecture. As today's network has diverse needs such as multimedia applications, QoS is also delivered on this TigerSwitch through IEEE802.1Q VLAN's, GVRP and priority queuing that ensure the smooth delivery of mission critical data and security of different multicast groups. SMC6708L2 INT is perfect for small or medium networks looking to strengthen its network backbone connection, or fiber-to-the-home applications for today's newly planned communities.

FEATURES	BENEFITS
Easy to install and integrate: 8-port 10/100 auto-MDIX port	GUI or Telnet options for easy network administration
Link aggregation creates high-speed data paths to servers or other switches	4-group RMON support for detailed monitoring of network management
VLAN support provides port VLANs and GVRP for auto-registration	MAC Address filtering for secure links
IGMP snooping reduces multicast traffic for maximum performance	Spanning Tree Protocol creates resilient links for increased stability
Compacted 10" case for easy fitting into restrict spaces	Limited Life Warranty

SMC Networks

TECHNICAL SPECIFICATIONS SMC6708L2 INT

PORTS
- 8 auto-MDIX 10BASE-T/100BASE-TX RJ-45 ports
- Built-in Network Management

NETWORK Interface
- 10BASE-T: RJ-45 UTP CAT. 3,4,5
- 100BASE-TX: RJ-45 UTP CAT. 5

LEDs
- System: Power
- Port: 10/100, Link/Activity, Duplex/Collision

DIMENSIONS
- 10 x 1.75 x 5.25 in
- 25x 38x 13.2 cm

WEIGHT
- 2 lbs / 6 oz

HUMIDITY
- Operating: 10% to 90% (non-condensing)

TEMPERATURE
- Operating: 32° to 113°F / 0° to 45°C
- Storage: -40° to 158°F / -40° to 70°C

WARRANTY
- Limited Lifetime

BUFFER ARCHITECTURE
- 2Mbits

SWITCH BANDWIDTH CAPACITY
- 1.6Gbps

AC INUT
- 100 to 240V, 50 to 60Hz

POWER SUPPLY
- Internal, auto-ranging transformer: 100 to 240VAC, 47 to 63Hz

POWER CONSUMPTION
- 19W max. @ 100-240 VAC

MAXIMUM CURRENT
- 0.16A @ 110V

SWITCH FEATURES
- Spanning Tree Protocol
- Store-and-Forward
- Flow Control
  - Full Duplex: IEEE802.3x
  - Half Duplex: back pressure
- VLAN support
  - Up to 128 groups; port-based or with 802.1Q
- VLAN tagging, GVRP for automatic VLAN learning
- Class of Service Supports two levels of priority
- Broadcast storm control
- Link Aggregation
- Port Mirroring

MANAGEMENT FEATURES
- In-Band Management
  - Telnet, Web-based HTTP, or SNMP manager
- Out-of-Band Management
  - RS-232 DB-9 console port Software Loading
  - TFTP in-band or Xmodem out-of-band
- MIB Support
  - MIB II (RFC 1213), Bridging MIB (RFC 1493), Ethernet-like
  - MIB (RFC 1643), RMON MIB (RFC 1757)

RMON SUPPORT
- Groups 1, 2, 3, 9 (Statistics, History, Alarm, Event)

STANDARD
- IEEE802.3 Ethernet, IEEE802.3u Fast Ethernet
- IEEE802.1D Spanning Tree Protocol
- IEEE802.1Q VLAN
- IEEE802.1P Priority Tags
- IEEE802.3x Full-Duplex, Flow Control
- SNMP (RFC 1157), RMON (RFC 1757), ARP (RFC 826), IGMP (RFC 1112), MIB II (RFC 1213), Ethernet-like MIB (RFC 1643), Bridge MIB (RFC 1493)

COMPLIANCES

CERTIFICATION
- CE Mark

EMISSIONS
- FCC Class A, CISPR Class A Immunity
- IEC 1000-4-2/3/4/6

SAFETY
- CSA/NRTL (CSA22.22950 & UL 1950), EN60950 (TUV/GS)

Contact

North America
38 Tesla
Irvine, CA 92618
1-800-SMC-4YOU
24/7 Technical Support

Europe/ Africa
Fructuos Gelabert 6-8
08970 Sant Joan Despí
Barcelona, Spain

Check www.smc.com for your local country contact information